

Director of Accounts Eileen Callahan 216/931-9546 eileen.callahan@penton.com **Account Executive** Carol Schumacher 216/931-9934 carol.schumacher@penton.com **Production Manager** Shaun Kelly 913/967-1829 shaun.kelly@penton.com Reprints Joel Kirk 216/931-9324 joel.kirk@penton.com

Vince Potochar 216/931-9336

Renton Custom Solutions





Your Resource on Efficient Water and Energy Systems online at www.greenmechanicalcontractor.com









CONTENTS

BY ROBERT GUENTHER There will be new requirements

for energy performance and indoor environmental quality. S GREEN NEWS Portland Federal Building goes

green; AHRI, DOE agree to regional efficiency standards.

10 GREEN MECHANICAL AWARDS GMC readers show off outstanding projects in our inaugural awards program. 11 FIRST PLACE RESIDENTIAL

La Jolla house has every conceivable green technology. 12 FIRST PLACE COMMERCIAL An Ohio middle school gets a green

makeover and finally works right.

14 MOST INNOVATIVE Contractor drills geothermal field from inside the basement. **16** GMA RUNNERS-UP

Our second and third place finishers built amazing projects. **20** HANDLING SOLAR CUSTOMERS

BY VIKTOR TCHERNIKOV Solar customers are making a huge investment and need special handling.

23 BUYERS GUIDE Our first annual directory of leading green mechanical and plumbing suppliers.

34 GREEN CALENDAR

28 GREEN PRODUCT SHOWCASE

wins national award from GMC Magazine Posted on April 22, 2009

LEED for Homes Residence in Longview





Other project highlights include: The refrigerant-to-water heat pump provides hot and chilled water to fan coils and radiant floors via buffer tanks. Domestic hot water (DHW) preheat is provided by the heat pump with final heat provided by an electric Tekmar controls provide three separate mix tempera-

14 GREEN MECHANICAL CONTRACTOR • WINTER 2009

tures for the six radiant zones.

ficult drilling conditions; each of the six loops is only 100-ft.

A direct digital control (DDC) system coordinates the equipment operation and provides dew point control and mixing; in the future, fan coils will be used for dehumidification using water below the room dew point, then the fan coil return water will be mixed with the water in the radiant floors to provide sensible radiant "One of the primary goals for this mechanical system was sustainability — we had to ensure that the wind turbine would provide enough energy to run the home year-round," says Brian Nelson, president, Nelson Mechanical Design, Inc., Vineyard Haven, Mass. "While first cost was important,

LEFT: The geology of the site made for a challenging geothermal

RIGHT: Six, 100-ft. geothermal loops were drilled through

installation.

system and low energy use made this installation attractive to the homeowner." A horizontal field was impossible due to the shape of the site, so a vertical - actually diagonal- installation was approved. The direct exchange system was chosen to minimize drilling costs and borehole depths. "Drilling was extremely difficult due to the geology of the site. The crew encountered 20 ft. of sand, then enormous 20-ft. boulders left over from the glacier that formed Martha's Vineyard at the end of the last Ice Age, then layers of

sand, then more boulders," Nelson says. "The pounding the

drill rig endured was tremendous. Fortunately, the direct

exchange borehole diameter was only 4 in. instead of 6 or 8

in., as is common with closed-loop glycol systems. The effort was worth it as the entire manifold system for the vertical

borehole field is directly under the mechanical room floor

long-term energy efficiency and reliability were paramount. The very low maintenance requirements of a geothermal

with little chance for damage from future landscaping or construction projects." Timber frame made the installation of ductwork difficult, so radiant space heating (and future space cooling) and three fan coils for heating, cooling, and dehumidification were installed in various zones throughout the residence. "Plastic water heaters were chosen to greatly reduce longterm maintenance as the water quality was fairly aggressive," Nelson continues. "The 2-in. foam insulation also greatly reduced standby loss, which allowed for more efficient loading of the geothermal heat pump." The sophisticated DDC schemes allow for optimized system operation and enabled Nelson to reduce the size and

cost of the mechanical plant. He estimates the homeowner

will save 40% in annual energy costs as compared to a tradi-

greenmechanicalcontractor.com

tional fossil fuel-burning residence. 💍